

Thermal Noise Reduction Using Multilayer Insulation in LIGO Gravitational Wave Detectors

The Laser Interferometer Gravitational-Wave Observatory (LIGO) detects gravitational waves by measuring minute changes in the lengths of its kilometer-scale interferometer arms with unprecedented precision. Such extreme sensitivity requires stringent suppression of thermal and environmental noise sources that can mask or mimic gravitational-wave signals. The multilayer insulation (MLI) technique plays an important role in thermal management within vacuum and cryogenic subsystems associated with advanced gravitational-wave detectors. MLI, composed of multiple alternating layers of low-emissivity reflective films and insulating spacers, significantly reduces radiative heat transfer in high-vacuum environments. By minimizing temperature fluctuations and thermal gradients around critical components such as vacuum chambers, suspension systems, and optical assemblies, MLI helps maintain dimensional stability and reduces thermally induced mechanical noise. In proposed and next-generation cryogenic upgrades, effective radiative shielding using MLI becomes even more crucial for preserving mirror quality and limiting thermal drift. Thus, the implementation of multilayer insulation contributes indirectly but significantly to enhancing detector sensitivity, operational stability, and the long-term performance of LIGO and future gravitational-wave observatories.

Author: Dr SINGH, Damini (Department of Physics, Gujarat Arts and Science College, Ellisbridge, Ahmedabad, Gujarat, 380006)

Co-authors: Dr SARASWAT, Kapil (Department of Physics, School of Engineering, Dayananda Sagar University, Bengaluru - 562112, India); Prof. SINGH, Venkatesh (Department of Physics, Central University of South Bihar, Gaya - 824236, India)

Presenter: Dr SINGH, Damini (Department of Physics, Gujarat Arts and Science College, Ellisbridge, Ahmedabad, Gujarat, 380006)