



A DCAT 3 Catalog Model for Semantic Interoperability in EOSC


Sharing heterogeneous resources across the Federation without losing information

EOSC Symposium 2026 · Florence · Track 3 – EOSC Federation IF, architecture and data-related policies

Christelle Pierkot · CNRS — Data Terra EOSC Node, deputy coordinator

Julien Homo · Foxcub — Data Terra EOSC Resource Catalogue

Alessandro Rizzo · IRD — Data Terra EOSC Node, coordinator



eosc A multidisciplinary thematic node

Context · Earth & environmental sciences, research products and services



TWO RESEARCH INFRASTRUCTURES



French research infrastructure for Earth system data



NFDI4Earth

German NFDI consortium for Earth system sciences

DISCIPLINES

Atmosphere

Ocean

Solid Earth

Land surfaces

Biodiversity

WHAT THEY BRING — EACH WITH ITS OWN STANDARD

- **Data** ISO 19115, GeoDCAT-AP
- **Software** CodeMeta
- **Publications** DataCite
- **Services** EOESC service profile

THE CHALLENGE

How can a Node share its resources without losing information, while still meeting EOESC Federation requirements?

eosc Semantic interoperability by design



Following the EOESC Semantic Interoperability Task Force recommendations — and going further

TF recommendation	Priority	How the Data Terra catalogue implements it
2.2.1 Latest DCAT as baseline, reuse application profiles	Critical	DCAT 3 pivot for every resource, aligned with DCAT-AP and GeoDCAT-AP
2.2.2 Standard domain vocabularies and identifier schemes	Critical	Values are SKOS concepts referenced by IRI; ROR, ORCID, SPDX, typed PIDs
2.2.3 Dedicated artefacts for outputs other than data	Important	CodeMeta for software, DataCite for publications, MOD for semantic artefacts
2.2.5 Modelling and validation alongside the profile	Useful	SHACL conformance gate before anything is exposed
2.4.1 Semantic artefacts managed through a catalogue	Critical	Disciplinary vocabularies resolved through EarthPortal, the Earth-science SAC

...and further: the node keeps the full, rich description and projects a compliant view to the EOESC EU Node.



Source: EOESC-A Semantic Interoperability TF, Deliverable 2 — Practical semantic interoperability recommendations for the EOESC Federation (2026)

eosc One DCAT 3 pivot for every resource


Native descriptions in, one knowledge graph, several standard projections out



NATIVE SOURCES



PROJECTIONS



COMMON CORE

identity · title & description · dates · publisher, creators, contacts · licence & access rights · themes & keywords · spatial & temporal coverage · distributions · typed identifiers (adms:identifier) · equivalences (owl:sameAs) · provenance (PROV-O)

eosc A typed dcat:Resource, not nine subclasses



Plain DCAT 3, with the kind of resource carried by a SKOS concept

DCAT 3 only has classes for datasets, data services and catalogues. Forcing software, publications or other research product into dcat:Dataset would state something false.

So every record is a **dcat:Resource**, and its kind is a concept in **dct:type**

No custom application profile to maintain; the type vocabulary can evolve without touching the model.

```
# Dataset .
<https://w3id.org/earth-data/resource/4c6312e0-...>
  a dcat:Resource, dcat:Dataset ;
  dct:type coar:c_ddb1 ;
  dct:title "Chemical and mineralogical composition
    of southern Africa dust aerosols" ;
  dcat:theme <terra-vocabulary.org/.../c_4064c319> ;
  dct:license spdx:CC-BY-4.0 ;
  dct:accessRights coar:c_16ec ;
  adms:identifier [ dct:type "DOI" ;
    skos:notation "10.57932/b4373977-..." ] ;
  dct:source <terra-vocabulary.org/id/DataSet/640a...> ;
  prov:hadPrimarySource <doi.org/10.57932/b4373977-...> .
```

```
# Publication .
<https://w3id.org/earth-data/resource/710e0264-...>
  a dcat:Resource ;
  dct:type coar:c_6501 ; # journal article
  dct:title "A real scale application of a novel set of
    spatial and similarity features ... from DAS data" ;
  bibo:journal "Geophysical Journal International" ;
  dct:license <creativecommons.org/licenses/by/4.0/> ;
  dct:accessRights coar:c_abf2 ;
  adms:identifier [ dct:type "DOI" ; skos:notation
    "10.1093/gji/ggae382" ], [ dct:type "HAL" ;
    skos:notation "insu-04763870" ] ;
  owl:sameAs <doi.org/10.1093/gji/ggae382> ;
  prov:hadPrimarySource <insu.hal.science/insu-04763870v1> .
```

NINE RESOURCE TYPES – ONE MODEL

Dataset

Research software

Publication

Service

Semantic artefact

Project

Training material

Deployable application

Interoperability guideline

eosc Values are concepts, not strings

Controlled vocabularies referenced by IRI, for every resource type



`dct:type`
COAR Resource Types

`dcat:theme (data)`
Data Terra Thesaurus

`earthdata:scientificDomain`
EuroSciVoc

`Service category`
EOSC Service Classification

`Service TRL, access type`
EOSC vocabularies

`dct:license`
SPDX licence list

`dct:accessRights`
COAR Access Rights

`dct:publisher, funders`
ROR

`dct:creator, contributor`
ORCID

`dct:language`
ISO 639

`Related identifiers`
DataCite RelationType

`Coordinate Reference System`
OGC EPSG

Why it matters A concept IRI carries its label, definition and alignments: a node that receives the record can filter, translate and reason on it — a free-text string only gets matched character by character.

eosc Identity and history of every record

Persistent identifiers on w3id, provenance with PROV-O



“PERSISTENT” IDENTIFIERS

w3id.org/earth-data/...

- **Node-minted, stable, resolvable**

Every record gets its own IRI, independent of the source system

- **Native PIDs kept, typed**

DOI, SWHID, HAL-ID, Handle as adms:identifier with their scheme agency

- **Source identity preserved**

Original IRIs as owl:sameAs; federated records keep their node's identifier

PROVENANCE WITH PROV-O

Why: every harvested record keeps a machine-readable link to its source, so it can be traced back, credited and re-harvested.

- **Link to the source**

prov:hadPrimarySource → the original record

- **Credit the producers**

prov:wasAttributedTo → authors and organisations, with their role when known


- **Trace our processing**

prov:wasGeneratedBy → the “DataTerra harvest” activity and each enrichment step

Queryable like any other metadata, and carried over into the EOSC exports.

eosc Rich inside, compliant outside

EOSC EU Node (EEN) compatibility is a projection of a richer model



BETWEEN NODES: WHY A RICH DCAT 3 JSON-LD OUTPUT IS NEEDED

EEN formats — mandatory, but not sufficiently expressive

- Fixed field set per channel (OpenAIRE / DataCite, EOSC profile)
- Domain extensions dropped: GeoDCAT-AP, CodeMeta, MOD
- Concepts reduced to labels, provenance reduced to names



DCAT 3 JSON-LD — node to node, without reduction

- The full pivot record, as stored in the node
- Vocabularies, identifiers, provenance kept as IRIs
- Peers align, deduplicate and enrich — no loss

eosc EOSC Federation: how nodes find and read each other



Federation · discovery through /.well-known, tested with the LSCN node

DISCOVERY ·

<https://resources.earth-data.eu/.well-known/eosc-federation/node>

Why it is needed In a federation without a central hub, a node must find the others' catalogues, formats and support services by itself — not through URLs exchanged by e-mail and configured by hand.


```
node_endpoint: "https://resources.earth-data.eu/.well-known/eosc-federation/node"
capabilities:
  0: { capability_type: "Resource Catalogue", endpoint: "https://resources.earth-data.eu/api/resources?eoscTypes=Research%20Product&format=dc", ... }
  1: { capability_type: "Resource Catalogue", endpoint: "https://resources.earth-data.eu/oai", version: "0.2.56", ... }
  2: { capability_type: "Service Catalogue", endpoint: "https://services.earth-data.eu/api/resources?types=Service&format=dc", version: "0.2.56", ... }
  3: { capability_type: "Service Catalogue", endpoint: "https://services.earth-data.eu/services", version: "0.2.56", ... }
  4: { capability_type: "AAI", endpoint: "https://sso.earth-data.fr/realms/gaia-data/.well-known/openid-configuration", protocol: "OIDC", ... }
  5: { capability_type: "Monitoring", status: "PLANNED" }
  6: { capability_type: "Accounting", status: "PLANNED" }
  7: { capability_type: "Helpdesk", status: "PLANNED" }
  8: { capability_type: "Order Management", status: "PLANNED" }
  9: { capability_type: "Application Workflow Management", status: "PLANNED" }
node_details: { name: "Data Terra EOSC Node", url: "https://www.earth-data.eu", description: "The Data Terra EOSC Node." }
```

WHAT IT BRINGS

- **One predictable URL per node** — all a peer needs to know
- **Machine-readable capabilities** — endpoints, formats, status
- **Self-configuring harvesters** — no bilateral set-up

Test with the Life Science Connect node

23 of our services read by LSCN · 10 LSCN services ingested



Our catalogue: LSCN services (green badge) among Data Terra ones

- **Found via descriptor**, 0 warnings
- **DCAT** ≈ 1:1 onto pivot
- **EOSC Beyond** format agreed
- **Open**: identity & provenance

eosc Testing node-to-node exchange with ENVRI



DEDUPLICATION MECHANISM

DATASET	EOSC RESEARCH PRODUCT	5 RECORDS DUPLICATED · CROSS-CATALOGUE
Argo float data and metadata from Global Data Assembly Centre (Argo GDAC)		
MTEP	https://w3id.org/earth-data/resource/1b2a81fd-3eff-5129-a5ce-eed32b17fd98	
ENVRI-HUB NEXT	https://w3id.org/earth-data/resource/df502b0b-1822-53e7-bb2e-5b28c0ffd475	
ENVRI-HUB NEXT	https://w3id.org/earth-data/resource/36ac37c3-871d-55ae-a14f-76e54b8086b2	
ENVRI-HUB NEXT	https://w3id.org/earth-data/resource/b2b6b718-d339-5ba9-8bcb-82118b6638bb	
ENVRI-HUB NEXT	https://w3id.org/earth-data/resource/015304ea-68b3-58d7-ae6a-906df6e935c7	

DATASET	EOSC RESEARCH PRODUCT	2 RECORDS DUPLICATED · CROSS-CATALOGUE
IAGOS Daily mean profiles at 4 levels - L3		
AERIS	https://w3id.org/earth-data/resource/3751c1fd-7628-5c56-9ad8-71758983ee87	
ENVRI-HUB NEXT	https://w3id.org/earth-data/resource/c4611458-21a9-5f7f-8a27-f3f125980968	

DATASET	EOSC RESEARCH PRODUCT	2 RECORDS DUPLICATED · CROSS-CATALOGUE
IAGOS Daily aggregated regional data at 3 levels - L3		
AERIS	https://w3id.org/earth-data/resource/b566b470-79e1-5d27-8b11-1c0f1f3d3a79	
ENVRI-HUB NEXT	https://w3id.org/earth-data/resource/cec0ef85-ff63-5d52-9c7b-2ab5088a55e0	

128

ENVRI records
indexed

72

datasets

56

services

0

errors

After deduplication 56 datasets + 55 services visible

MECHANISM — GROUP, NEVER MERGE OR DELETE

- 1 Keep identity** own w3id @id; source ID and URI kept
- 2 Match** same DOI / PID, or title + declared type
- 3 Cluster** shared clusterId + confidence level
- 4 Keep all** one shown, every member kept

WHAT THE CLUSTERS SAY

- **IAGOS × 2 — true duplicates**
same object in AERIS and ENVRI (DOI 10.25326/638, /639)
- **Argo — strong title match**
but granularity issue

Lesson shared DOIs make true duplicates obvious; title matches expose the granularity question. WORK in progress, not yet in production.

Layer 1 · common floor

EEN profile for every node — mandatory, minimal, central discovery

Layer 2 · rich contract

DCAT 3 pivot + shared vocabularies between neighbouring and thematic nodes that already use enriched models

- 1 Rich and compliant is possible**
one DCAT 3 pivot, several standard projections
- 2 Identifiers and granularity are the hard part**
more than syntax or serialisation
- 3 Next: test with more nodes**
DTO, national nodes, ...

“There is a consensus in the nodes that exposing rich domain catalogue resources would be necessary to maximise the benefits of federating EOSC node catalogue resources.” — EOSC United, node interviews

Thank you · christelle.pierkot@cnrs.fr, julien.homo@foxcub.fr, alessandro.rizzo@ird.fr