



Contribution ID: 1110  
Contribution Type: **Oral (Student, Not in Competition)** / **Orale (Étudiant(e), pas dans la compétition)**

Type: **Oral (Student, Not in Competition)** / **Orale (Étudiant(e), pas dans la compétition)**

## Hollow-core photonic Bragg fiber for bulk and surface sensing applications

*Tuesday 14 June 2016 14:30 (15 minutes)*

We demonstrate a hollow-core photonic Bragg fiber for bulk and surface sensing applications. The sensor operates on a resonant sensing modality. Variation in the fiber core effective refractive index modifies the bandgap guidance of the fiber, leading to a spectral shift in the fiber transmission spectrum. As a demonstration for the bulk sensing application, we apply the fiber sensor to detect refractive index of analyte filling in the fiber core, a sensitivity of 1500nm/RIU is achieved. As a demonstration for the surface sensing application, we use it to monitor the dissolution dynamic of a thin film coated on the fiber core inner surface, the obtained surface sensitivity is found to be 0.05nm/nm. The proposed sensor presents a 'one fiber' solution for both bulk and surface sensing applications, which is promising for the development of a new generation of the fiber-based biosensors.

**Author:** LI, Jingwen (polytechnique de montreal)

**Co-author:** Prof. SKOROBOGATIY, Maksim (Ecole polytechnique de Montreal)

**Presenter:** LI, Jingwen (polytechnique de montreal)

**Session Classification:** T2-5 Photonics I: Applications (DAMOPEC-DPP) / Photonique I : applications (DPAMPC-DPP)

**Track Classification:** Division of Atomic, Molecular and Optical Physics, Canada / Division de la physique atomique, moléculaire et photonique, Canada (DAMOPEC-DPAMPC)