



Contribution ID: 53

Type: **Poster Presentation**

Comparison of breakdown voltage of N₂, CO₂, SF₆, N₂-SF₆ and CO₂-SF₆ mixtures: Seeking substitutes for SF₆ for high voltage apparatus

Wednesday 6 July 2016 14:40 (20 minutes)

Due to excellent and outstanding properties in both electrical insulation and current interruption performances, sulfur hexafluoride gas, SF₆, is the most used gas in high voltage power equipment such as circuit breakers (GCB), switchgears (GIS), and transmission lines (GIL) since 1960s. ; SF₆ is one of the best insulators gas known to date. However, by its excessive size and life span (several centuries or even thousands of years), the SF₆ molecule is an agent aggravating the greenhouse effect; its global warming potential (GWP) is 23900 times that of CO₂. In 1997, the Kyoto Protocol (COP 3) labeled SF₆ as one of the global warming gases and began to control its use and emission into the atmosphere. Thus, the international recommendations tend to heavily restrict or even prohibit in the future, its use for preserving the environment. Since then, important researches have been undertaken to find substitutes for SF₆ that have less impact on the environment, and compatible dielectric and current interrupting capabilities. Various gases have been considered. Unfortunately all these gases present a high liquefaction temperature as well as a high price. To increase the liquefaction temperature, these gases can be mixed with N₂ and CO₂. Among these gases, c-C₄F₈ has a dielectric strength 1.25 to 1.31 times higher than that of SF₆ and its global warming potential (GWP) is 36 % lower than that of SF₆. However its liquefaction temperature is too high. The breakdown voltage of c-C₄F₈-N₂ mixture increases with pressure reaching an asymptote. Other mixtures that have been investigated include c-C₄F₈-CO₂, C₃F₈-CO₂, C₃F₈-N₂, C₂F₆-CO₂ and C₂F₆-N₂. Of the mixtures, 20 %C₃F₈ - 80 %N₂ shows the best performance. This mixture enables the GWP to be reduced and its dielectric properties are close to those of 20 %SF₆ - 80 %N₂ at 0.79 MPa. It clearly appears that it will be difficult to find a suitable substitute for high voltage power equipment even if the last years, some new gas mixtures that are under study seem interesting. In this paper, we present a comparison study of breakdown voltage of CO₂, N₂ and SF₆, and CO₂-SF₆ and N₂-SF₆ gas/mixtures under different types of voltage namely AC, DC and lightning impulse voltage in a sphere-sphere electrodes arrangement. The influence of percentage of SF₆ in CO₂ and N₂ and pressure are investigated. The equivalencies between breakdown voltage SF₆ and those of mixtures versus pressure are discussed. The economic and safety aspects are also analyzed.

Authors: Prof. BEROUAL, Abderrahmane (Ecole Centrale de Lyon, University of Lyon, Ampere Lab); Dr COULIBALY, Mamadou-Lamine (Ecole Centrale de Lyon, University of Lyon, Ampere Lab)

Presenter: Prof. BEROUAL, Abderrahmane (Ecole Centrale de Lyon, University of Lyon, Ampere Lab)

Session Classification: Poster 1-B

Track Classification: Dielectrics, Insulation, and Breakdown