



Contribution ID: 321

Type: **Poster Presentation**

## **Analysis of Fault Characteristics of Converter in VSC-HVDC**

*Thursday 7 July 2016 14:40 (20 minutes)*

The voltage source converter is an important part of VSC-HVDC (Voltage source converter based high voltage direct current) system which has low over-voltage and over current bearing ability and thus prone to various faults. In this paper, based on the VSC-HVDC system PSCAD/EMTDC simulation model, the mathematical model of DC voltage and current fluctuation component caused by AC single-phase break fault is established. Also, the mathematical model of fault AC current on both-side converters is built. Based on the research mentioned above, two VSC fault harmonic transfer patterns is studied. It is proved that n-th harmonic positive sequence on AC side of one-side fault converter will lead to (n-2)-th harmonics negative sequence and n-th harmonics positive sequence on the other VSC, and that n-th harmonics negative sequence on AC side of the fault converter will cause n-th harmonics negative sequence and (n+2)-th harmonics positive sequence on the other VSC.

**Author:** Mrs SUN, Xiaoyun (School of Communication and Information Engineering , Xi'an University of Science and Technology)

**Co-authors:** Mr GAO, Xin (Northwest Subsection of State Grid Corporation of China,); Dr SONG, Ying (State key laboratory of electrical insulation & power equipment, Xi'an Jiaotong University); Prof. JI, shengchang (State key laboratory of electrical insulation & power equipment)

**Presenter:** Mrs SUN, Xiaoyun (School of Communication and Information Engineering , Xi'an University of Science and Technology)

**Session Classification:** Poster 2-A

**Track Classification:** Power Electronics, Power Supplies, Prime Power, Rotating Machines, and Energy Converters