## 2018 IEEE International Power Modulator and High Voltage Conference



Contribution ID: 272

Type: Poster Presentation

## Development of low-impedance, variable pulse-width, high repetition rate, 400 kV modulator

A low impedance modulator made up of ceramic-loaded parallel-plate transmission line sections in a Marx configuration has been developed as a test bed for high power microwave sources. The generator has configurable impedance between 15 and 25 ohms, pulse-width between 50 and 200 ns, and can operate at repetition rates up to 100 Hz with a 200 kW high voltage power supply. The energy stored in the lowest impedance and longest pulse width setting is 2 kJ. A low inductance, 18 mm thick center-plane triggered rail switch has been developed around an SLA 3D printed pressure vessel. The generator design, implementation, and initial experimental results are discussed.

Authors: Dr CHAPARRO, Jordan (NSWCDD); Mr MCQUAGE, Matthew (NSWCDD); Dr CHEN, Yeong-Jer (NSWCDD)

Presenter: Dr CHEN, Yeong-Jer (NSWCDD)

Session Classification: Poster 3 - Power Modulator Systems and Applications

**Track Classification:** Repetitive Pulsed Power Systems, Repetitive Pulsed Magnetics, Accelerators, Beams, High Power Microwaves, and High Power Pulsed Antennas