



Contribution ID: 98 Contribution code: P2.30

Type: Poster

Application of three-ion ICRF scenarios for optimizing ion heating in the ramp-up phase in future tokamaks

Wednesday, October 4, 2023 4:00 PM (4 minutes)

The success of magnetic confinement fusion as energy source relies crucially on reaching high temperatures for the fuel D and T ions. In a fusion reactor, plasma heating with waves in the ion cyclotron range of frequencies (ICRF) is the only system capable to provide a large fraction of bulk ion heating. Furthermore, in view of better understanding non-linear physics of alpha heating in ITER and future reactors, generation of MeV-range ions with ICRF and studying different mechanisms on how fast ions impact the plasma dynamics becomes progressively more important. Recent progress with the development of three-ion ICRF scenarios have expanded the use of these scenarios from dedicated ICRF studies [1] to a flexible tool with a broad range of applications [2].

In order to maximize bulk ion heating of D-T \approx 50%-50% plasmas and increase T_i in the ramp-up phase with ICRF, ITER foresees the injection of a few percent of ^3He ions [3]. Because ^3He is a scarce gas, using the three-ion T-(IMP)-D ICRF scenario with a small amount of selected impurities (IMP) with $1/3 < (Z/A)_{\text{imp}} < 1/2$ as resonant absorbers was proposed in [4]. A fairly large number of low-Z and mid-Z impurities and their isotopes with $(Z/A)_{\text{imp}} \approx 0.44-0.46$ satisfy this criterion, including ^7Li , ^9Be , ^{11}B , ^{22}Ne , and Ar. Since these impurities have a higher atomic mass than ^3He ions, they transfer an even larger fraction of the absorbed RF power to bulk D and T ions via Coulomb collisions.

The potential of ^7Li and ^9Be impurities ($n_{\text{imp}}/n_e \approx 1\%$) to absorb RF power efficiently in D-T plasmas was demonstrated at TFTR and recently at JET-ILW [5]. In particular, in recent JET-ILW experiments with the three-ion T-(^9Be)-D ICRF scheme, a strong increase of T_i with ICRF was observed, in line with theoretical predictions. The experimental demonstration of this scenario at JET-ILW thus allows to extend the list of potential applications of three-ion ICRF scenarios in ITER and future fusion reactors.

At the moment, ITER is considering to switch from the Be/W to the full-W first wall, thus motivating the need to re-assess the potential of three-ion T-(IMP)-D ICRF scenarios in the absence of ^9Be . In this contribution, we evaluate promising extrinsic impurities and the range of their concentrations for efficient bulk ion heating in D-T plasmas, with a focus on the plasma parameters in the ramp-up phase. We also discuss the potential of these novel ICRF scenarios for their applications in future high-magnetic field and high-beta spherical tokamaks [6, 7].

References:

- [1] Ye.O. Kazakov et al., Nature Physics 13, 973 (2017)
- [2] Ye.O. Kazakov et al., Phys. Plasmas 28, 020501 (2021)
- [3] R. Dumont et al., Nucl. Fusion 53, 013002 (2013)
- [4] Ye.O. Kazakov et al., Phys. Plasmas 22, 082511 (2015)
- [5] Ye.O. Kazakov et al., "Progress With Applications of Three-Ion ICRF Scenarios for Fusion Research: A Review", AIP Conf. Proc. (2023), accepted
- [6] M. Gryaznevich et al., this conference
- [7] M. Romanelli et al., this conference

Author: KAZAKOV, Yevgen

Co-author: Prof. ONGENA, Jeff (Laboratory for Plasma Physics, LPP-ERM/KMS, Brussels, Belgium)

Presenter: KAZAKOV, Yevgen

Session Classification: Poster session: 02